



Job Name \_\_\_\_\_ Item # \_\_\_\_\_  
 Location \_\_\_\_\_  
 Engineer \_\_\_\_\_ Contractor \_\_\_\_\_  
 PO # \_\_\_\_\_ Tag \_\_\_\_\_  
 Representative \_\_\_\_\_

Oatey Ice Maker boxes can be used in commercial or residential applications which require supply valves recessed into the wall.

Valves	ASME A112.18.1 / CSA B125.1 NSF / ANSI 61 & 372
Water Hammer Arrestors	ASSE 1010
Boxes	IAPMO-Listed, PS-54



(All dimensions in inches)

- 125 PSI Maximum working pressure
- Right or left hand installation
- Box made of high impact polystyrene
- Valves comply with requirements of NSF 61, Section 9
- Available with Copper, CPVC, PEX and Push Connect connections
- Snap-on faceplate frame
- US Patent # D 428,117

[A]:	Box Width	4.05"	[E]:	Box Depth	2.35"
[B]:	Box Height	5.60"	[F]:	Faceplate Width	5.00"
[C]:	Box Opening Width	3.03"	[G]:	Faceplate Height	5.89"
[D]:	Box Opening Height	3.98"	[H]:	Faceplate Depth	0.50"

